



## **DP-530 SE/530L SE**

Fast and  
ruggedized simplicity



### **HIGHLIGHTS AT A GLANCE:**

- Easy-to-read control panel
- Simple drop-in paper loading
- High-speed signature printing and extensive font and graphic capabilities
- Popular printer emulations provide compatibility
- DP-530 Receipt version / DP-530L Label version
- IP54 per IEC 529

# DP-530 SE/530L SE

With the Tally Dascom DP-530 SE series you can concentrate on your job and not on the printer. Although the printer is up to 10% smaller and 40% lighter than comparable models, it makes no compromises. A variety of interfaces and emulations allow the use of DP-530 SE/DP-530L SE in different environments.

Whether water, dust or vibrations, this printer operates reliably. Whether in the basic variant DP-530 SE for receipt documents or in the label version as DP-530L SE. Thanks to different holders, the printer can easily install on mobile dollies or in vehicles.

## TECHNICAL SPECIFICATIONS

<b>Print speed</b>	Up to 5 inch/sec (127 mm/sec)
<b>Resolution</b>	203 dpi (8 dots/mm)
<b>Lifetime print head</b>	50 km
<b>Memory</b>	256 MB FLASH, 512 MB DRAM
<b>Print width</b>	Up to 72 mm
<b>Interfaces Standard</b>	USB 2.0
<b>Interfaces Optional</b>	Bluetooth (4.0) or WiFi (802.11 b/g/n)
<b>Bluetooth</b>	Compatible Bluetooth 2.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE
<b>WiFi</b>	Encryption: WEP, WPA-PSK/TKIP, WPA2-AES, 802.1x EAP with TLS, TTLS, LEAP, FAST, PEAP
<b>Administration</b>	Internal Website
<b>Emulations</b>	ESC/POS, ZPL II, CPCL, EPL, PostScript, PDF
<b>Roll diameter</b>	Max. diameter 50,8 mm for DP-530 and 66 mm for DP-530L
<b>Roll capacity</b>	Approx. 28,6 m (equals 188 6" receipts) for DP-530 Approx. 52 m (equals 346 pcs. 6" labels) for DP-530L
<b>Battery</b>	Rechargeable 3 cells Lithium-Ion (3.000 mAh) Endurance more then 3.500 inchs per charge/8 hours shift without WiFi Charging time 2 hours
<b>Weight</b>	0,66 kg (incl. battery) for DP-530 0,69 kg (incl. battery) for DP-530L
<b>Dimensions</b>	117 x 155 x 69 mm (W x D x H) for DP-530 117 x 155 x 79 mm (W x D x H) for DP-530L
<b>Voltage</b>	12/24 V
<b>Temperature</b>	-18° to +50° C (printing); -20° bis 60° C (storage)
<b>Humidity</b>	10% to 90% rel. humidity
<b>MTBF</b>	10.000 hours
<b>Drivers</b>	Windows 8/8.1/10 and Server 2012/2016/209; Android; iOS (only WiFi)
<b>Certifications</b>	CE, FCC Class B, UL, E1

### Configurations:

• <b>DP-530 SE</b>	Receipt model	• <b>DP-530L SE</b>	Label model
• <b>DP-530 SE BT</b>	Receipt model with Bluetooth	• <b>DP-530L SE BT</b>	Label model with Bluetooth
• <b>DP-530 SE WiFi</b>	Receipt model with WiFi	• <b>DP-530L SE WiFi</b>	Label model with WiFi

**DASCOM GB Ltd**  
Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

**DASCOM Europe GmbH**  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047